

# MATERIAL SAFETY DATA SHEET

REV005

Date:20 August 2019

## Section 1 Identification

|              |     |
|--------------|-----|
| HEALTH       | [2] |
| FLAMMABILITY | [0] |
| REACTIVITY   | [0] |
| PROTECTION   | [E] |

Product Name: COLOURED HARDENER  
Chemical Name: Mixture  
Chemical Family: Mixture  
Chemical Formula: Mixture  
Manufacturer/Supplier:  
FIBERMAR (MKT) LIMITED. KW6  
Corradino Ind. Est. Paola PLA3000  
MALTA TEL:77632019

## Section 2 Composition/Information on Ingredients

| Composition                | Weight | OSHA TWA   | ACGIH TLV             | CAS Number |
|----------------------------|--------|--|-----------------------|------------|
| Silica, Crystalline Quartz | 60-90% | 0.1 mg/m <sup>3</sup>  | 0.1 mg/m <sup>3</sup> | 14808-60-7 |
| Cement                     | 10-60% | 10 mg/m <sup>3</sup> (Total)<br>5 mg/m <sup>3</sup> (Respirable) | 10 mg/m <sup>3</sup>  | 65997-15-1 |

## Section 3

### Hazards Identification

#### Emergency Overview:

Warning! Harmful if inhaled. Irritating to eyes and skin. May cause delayed lung injury (silicosis). Cancer hazard. Risk of cancer depends on duration and level of exposure.

**Acute Exposure:** Airborne particles will irritate the eyes and may cause temporary but reversible respiration difficulties. Cement is a severe eye irritant. In combination with water, it may cause alkali burns.

**Chronic Exposure:** Repeated inhalation of respirable silica in excess of the TWA over extended periods of time may result in irreversible fibrosis of the lungs (silicosis).

#### Signs and Symptoms of Exposure:

Inhalation - Undue coughing, wheezing, and breathlessness.

Eyes - Irritation, inflammation or abrasion of the eye.

Skin - Dryness, itching, rashes and burns may develop following skin contact. Dermatitis or skin sensitization may develop after repeated or prolonged contact.

Ingestion - May cause discomfort if swallowed.

**Medical Conditions Generally Aggravated by Exposure:** Dermatitis, pulmonary conditions and diseases.

## MATERIAL SAFETY DATA SHEET

REV005

Date:20/08/ 2019

### COLOURED HDN

#### Section 4

##### First Aid Measures

###### Emergency and First Aid Procedures:

Inhalation - If inhaled, or if difficulty in breathing is experienced, move to fresh air. If coughing, irritation, difficulty in breathing, or other respiratory symptoms persist or develop, get medical attention.

Skin - Wash thoroughly with soap and water. Remove soiled clothing and wash before reuse. If symptoms develop, get medical attention.

Ingestion - Get medical attention.

Eyes - DO NOT RUB EYES. Immediately flush thoroughly with plenty of water and get medical attention.

Note to physician - Mucosal injury following ingestion of this material may contraindicate the induction of vomiting in the treatment of possible ingestion.

##### Section 5 Fire and Explosion Hazard Data

|                                     |                               |
|-------------------------------------|-------------------------------|
| Flash Point (Method Used):          | None                          |
| Flammable Limits:                   | Not Applicable                |
| Extinguishing Media:                | Non Flammable Non Combustable |
| Special Fire Fighting Procedures:   | Not Applicable                |
| Unusual Fire and Explosion Hazards: | None Known                    |

#### Section 6

##### Accidental Release Measures

Steps to be Taken in Case Material is Released or spilled: Only qualified personnel who have read the product Tech-Data Bulletins and this MSDS should conduct these procedures. Persons not wearing protective equipment should be excluded from the area. Follow procedures in Section 8-Exposure Controls/Personal Protection. Avoid generating dust during recovery or disposal. Collect in labeled waste container.

#### Section 7

##### Precautions for Safe Handling and Use

Precautions to be taken in Handling and Storing: Follow personal protection procedures (Section 8) when handling the material. Store in a cool, dry, wellventilated area, in unopened original packaging or in tightly closed labeled containers. Protect from physical damage. Avoid contact with acids and other oxidizers. Avoid moisture; moisture may result in product hydration.

## MATERIAL SAFETY DATA SHEET

REVO05

Date: 20/08/ 2019

COLOURED HDN

### Section 8

#### Exposure Controls / Personal Protection

Ventilation/Engineering Controls: Adequate ventilation and sufficient local exhaust as needed to maintain exposure below TWA and TLV limits.

Respiratory Protection: Wear dust (particulate) respirator (NIOSH TC-84A approved). For respiratory protection guidelines refer to OSHA 29 CFR 1910.134.

Eye Protection: Wear safety goggles. Wearing of contact lenses when working with this product is not recommended.

Skin Protection: Wear impervious gloves.

Other Protective Clothing or Equipment: Wear suitable protective clothing to minimize skin contact.

Work/Hygienic Practices: Minimize exposure in accordance with good hygienic practice. Wash with soap and water immediately after handling.

### Section 9

#### Physical and Chemical Characteristics

|   |   |
|---|---|
| Boiling Point:                            | Not applicable                          |
| Vapor Pressure (mm Hg.):                  | Not applicable                          |
| Vapor Density (Air = 1 ):                 | Not applicable                          |
| Solubility in Water:                      | Slight                                  |
| Specific Gravity (H <sub>2</sub> O = 1 ): | Approximately 2.7-3.0                   |
| Melting Point:                            | Not applicable                          |
| Evaporation Rate (Butyl Acetate = 1 ):    | Not applicable                          |
| Volatile Organic Compounds:               | Nil                                     |
| Appearance and Odor:                      | Gritty powder. Various colors. No odor. |

### Section 10

#### Stability and Reactivity

Stability: Stable

Conditions to Avoid: Product reacts (hydrates) at a slow, controlled rate when mixed with water releasing minimal heat.

Incompatibility (Materials to Avoid): Strong oxidizing agents such as strong organic and inorganic acids. Acids will react with cement.

Hazardous Decomposition or By-products: No hazardous reaction under normal conditions.

Hazardous Polymerization: Will not occur.

# MATERIAL SAFETY DATA SHEET

REV005.

Date:20/08/ 2019

COLOURED HDN

## Section 11

### Toxicological Information

Health Hazards (Acute and Chronic):

Airborne particles will irritate the eyes and may cause temporary but reversible respiration difficulties. Cement, in combination with water, may cause alkali burns. Repeated inhalation of respirable silica in excess of the TWA over extended periods of time may result in irreversible fibrosis of the lungs (silicosis). IARC- The International Agency for Research on Cancer classifies quartz as Group 1 - probably carcinogenic to humans.

## Section 12

### Ecological Information

Aquatic Toxicity Rating: Aquatic toxicity rating not determined. The addition of products containing cement to water will, however, cause the pH to rise and may therefore be toxic to aquatic life in some circumstances. Therefore, all possible efforts should be made to keep the product away from drains, surface and ground water, and soil.

## Section 13

### Disposal Considerations

Waste Disposal Method:

Follow personal protection procedures (Section 8) when disposing of material. Disposal of all residual or recovered product must be in accordance with all applicable federal, state, and local regulations.

## Section 14

### Transport Information

DOT Hazard Class: Not regulated

## Section 15

### Regulatory Information

International Regulations: Consult the regulations of the importing country.

## Section 16

### Other Information

Before using this product: Completely read the Fibermar (MKT) Tech-Data Bulletin on TopCoat and/or Glamour Coat and the product label.

## WARRANTY

Since no control is exercised over product use, Fibermar (MKT) Limited represents and warrants only that its products are of consistent quality within manufacturing tolerances.

## MATERIAL SAFETY DATA SHEET

REV005

COLOURED HDN

Date:20/08/ 2019

NO OTHER ORAL OR WRITTEN REPRESENTATION OR STATEMENT OF ANY KIND, EXPRESS OR IMPLIED, NOW OR HEREAFTER MADE IS AUTHORIZED OR WARRANTED BY FIBERMAR (MKT) LIMITED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Liability for breach of contract, negligence, or on any other legal basis is limited to the lesser of refund or replacement of defective materials. FIBERMAR (MKT) LIMITED WILL NOT BE LIABLE FOR SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES, INCLUDING FOR DELAYS OR LOST PROFITS. Communication of this warranty and its limitations to end users is not the responsibility of FIBERMAR (MKT) LIMITED, but should be communicated by those in direct contract with the end user. Any claim regarding product defect must be received in writing within one year from the date of manufacture. No claim will be considered without such written notice or after the specified time interval. The end user shall determine the suitability of the products for the intended use and assumes all risks and liability in connection therewith.